

LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



**441 Series CF Compact
Wall Pack with Glass
Lens**

- Industrial Quality Fixture for Security Lighting, Parking Areas, & Walkways
- Programmed Start Electronic Highest Quality USA Ballast 120-277V
- Cross from MH or HPS to Compact Fluorescent for More Energy Savings*
- Minimum Start Temperature 0°F, -18°C
- UL Wet Location
- Die Cast Housing Bronze Aluminum Over Chromate Conversion Coating, Aluminum Reflector
- Molded Prismatic Borosilicate Glass Lens with Gasket
- Hinged Frame for Convenient Lamp Changes
- Compact Fluorescent Available From 18 to 42 Watts
- Photocell Available Upon Request
- Easy Access, O Ring Coin Plug Conduit Openings for Convenient Wiring Options
- Cool White Lamps Standard in Electronic Ballast, Warm White on Magnetic, Any Lamp Color Available Upon Request

Model	Lamp Type	Ballast Type	Watts	Ballast Voltage	Initial Lumens	Rated Average Lamp Life	Height	Width	Depth
44118ECF-L	18 Watt	Electronic	18	120-277	1200	10,000 Hrs.	9.5"	8.5"	7.625"
44122CF-L	22 Watt	Magnetic	22	120	1300	10,000 Hrs.	9.5"	8.5"	7.625"
44126CF-L	2x13 Watt	Magnetic	26	120	1600	10,000 Hrs.	9.5"	8.5"	7.625"
44126QECF-L	26 Watt	Electronic	26	120-277	1800	10,000 Hrs.	9.5"	8.5"	7.625"
44132ECF-L	32 Watt	Electronic	32	120-277	2400	10,000 Hrs.	9.5"	8.5"	7.625"
44136ECF-L	2x18 Watt	Electronic	36	120-277	2400	10,000 Hrs.	9.5"	8.5"	7.625"
44142ECF-L	42 Watt	Electronic	42	120-277	3200	10,000 Hrs.	9.5"	8.5"	7.625"

**Vertically Integrated Manufacturer
Made In USA**