

COMPACT FLUORESCENT 16" LARGE METAL FLOODLIGHT

LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



Compact Fluorescent 16" Large Metal Floodlight 640 Series

- Industrial Quality Fixture for Security Lighting, Parking Areas, Trees & Signs
- Programmed Start Electronic Highest Quality USA Engineered Ballast 120-277V
Cross from MH or HPS to Compact Fluorescent for More Energy Savings
- Minimum Start Temperature 0°F, -18°C
- Wet Location
- Flat Tempered Clear Glass Lens
- Die Cast Aluminum Housing, Bronze Powder Coating over Chromate Conversion Coating, Hinged Top Frame, Safety Cable Restraint, Coin Plugs with O Rings for Conduit and Photo Cell
- **All Mounting Options Available are Adders:** Stamped Steel Yoke, Swivel Wall Bracket, Extruded Mounting Arms or External Slip-fitter, or Direct Mount Pole Arm
- Compact Fluorescent Available From 36 to 126 Watts
- Cool White Lamps Standard on Electronic Ballast, Any Lamp Color Available Upon Request
- Photocell Available Upon Request, Voltage Specific
- Glare Shield (-GS) and Wire Guard (-WG) Adders Available, Also Available in White (-W)

Model	Lamp Type	Ballast Type	Watts	Ballast Voltage	Initial Lumens	Rated Average Lamp Life	Height	Width	Depth
64036ECF-L	2x18 Watt	Electronic	36	120/277	2400	10,000 Hrs.	14.625"	16.125"	7"
64052ECF-L	2x26 Watt	Electronic	52	120/277	3600	10,000 Hrs.	14.625"	16.125"	7"
64064ECF-L	2x32 Watt	Electronic	64	120/277	4800	10,000 Hrs.	14.625"	16.125"	7"
64072ECF-L	4x18 Watt	Electronic	72	120/277	4800	10,000 Hrs.	14.625"	16.125"	7"
640104ECF-L	4x26 Watt	Electronic	104	120/277	7200	10,000 Hrs.	14.625"	16.125"	7"
640128ECF-L	4x32 Watt	Electronic	128	120/277	9600	10,000 Hrs.	14.625"	16.125"	7"

**Vertically Integrated Manufacturer
Made In USA**