

**LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON**



**420 LED Series 12X12"  
Square Cut Off Wall**




- **Commercial And Industrial Non Glass** - Partial Cut Off Wall Mount - Vandal Resistant - Security Lighting For Parking, Stairwells, And Walkways - 120 - 277V - UL Wet
- **Textured Bronze Finish Die Cast** (A360 Aluminum Ingot) Housing, Chromate Conversion Coating With DuPont Powder For Powder Coat Finishes 3/4" Threaded Hubs For 1/2" Conduit Fittings, Gasket Standard, Polycarbonate Lens Molded With GE Lexan Containing UV Stabilizers 242R For Highest Temperature Ratings Aluminum Reflector For Optimum Light Distribution - Front Frame With Hood To Direct Light Downward **Adders:** Photo Cell (-PC) Stainless Steel Screws, Integrated Occupancy Sensor (-IS) Battery Back-Up (-BB)
- **Philips Fortimo LED Panels**, Low - Power LEDs In A Single Row Layout, Uniform Pattern, Push In Wire Connectors Enabling Easy Wiring, High Energy Efficiency And Long Lifetime, High Color Rendering And Excellent Color Consistency, (>80 CRI) And (>90 CRI Available) **Replaceable Panels And Driver - See Below For Lumens Per Color And Color Temperatures Available**
- **Philips Advance** Xitanium LED Driver With SimpleSet 1% Dim 0-10V Dimming, Operating Temperature - 20°C(-4°F) To +50 (122°F), PF>0.9, THD<20%, 120-277V, Audible Noise<24dB Class A, FCC Title 47 Part 15 Class A

Model	LED Panels System Watts	Initial Lumens	Driver Voltage	Rated Life Hrs	Dimensions		
					H	W	D
420LED2X6-50	2X6 = 9W	1100	120 - 277V	50K	12.375"	12.375"	9"
420LED3X6-50	3X6 = 12W	1650	120 - 277V	50K	12.375"	12.375"	9"
420LED4X6-50	4X6 = 15W	2200	120 - 277V	50K	12.375"	12.375"	9"
420LED5X6-50	5X6 = 18W	2750	120 - 277V	50K	12.375"	12.375"	9"
420LED6X6-50	6X6 = 22W	3300	120 - 277V	50K	12.375"	12.375"	9"
420LED7X6-50	7X6 = 25W	3850	120 - 277V	50K	12.375"	12.375"	9"
420LED8X6-50	8X6 = 28W	4400	120 - 277V	50K	12.375"	12.375"	9"

Lumens Per 1 X 6" Panel = 3000K = 520 Lumens 3500K = 530 Lumens 4000K = 540 Lumens 5000K = 550 Lumens

Specify Color At The End Of Model Number (-50, -40, -35, -30) Lumens Per Color Above



**Vertically Integrated Manufacturer  
Made In USA**