



LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



**150 LED Open Faced
Architectural Round**



Deep



Medium Is Standard



Shallow

- Decorative Commercial Grade - High Abuse Versatile, Vandal Resistant - Used In Schools, Exterior Walkway, Stairwells - Wall Or Ceiling Mount 120 – 277V **UL Wet**
- Die - Cast Marine Grade Aluminum Housing In **Shallow (S), Medium Standard** And **Deep (D)** Heavy Duty Gaskets, Polycarbonate Injection Molded Guards With **Matching Pans: White (W), Black (B), Bronze(BZ)** Adder For **Titanium (TI)** Polycarbonate Injection Molded Lens: **Opaque(OP) Frosted Ribbed (FR), Clear Ribbed (CR)** Tamper Proof Steel Screws Adders: Emergency **Battery Back-Up (-BB) Integrated Occupancy Sensor (IS)Photo Cell (PC)**
- **Philips Fortimo LED Panels**, Low - Power LEDs In A Single Row Layout, Uniform Pattern, Push In Wire Connectors Enabling Easy Wiring, High Energy Efficiency And Long Lifetime, High Color Rendering (>80 CRI) **>90 Available** And Excellent Color Consistency - **Replaceable Panels And Driver** See Below Lumens Per Color Variations And Color Temperature Options
- **Philips Advance Xitanium LED Driver With SimpleSet** 1% Dim, 0-10V Dimming, Operating Temperature -20°C (-4°F) To +50° (122°F), PF>0.9, THD<20%, 120-277V, Audible Noise<24dB Class A, FCC Title 47 Part 15 Class A
- **Other Wattages And Combinations Available**


Model	LED Panels System Watts	LED Lumens	Driver Voltage	Rated Life Hrs	Depth	Length
150LEDSBOP1X650	1X6 = 6W Shallow	550	120 - 277V	50K	3.75"	13.183"
150LEDSBOP2X650	2X6 = 9W Shallow	1100	120 - 277V	50K	3.75"	13.183"

150LEDBOP1X6-50	1X6 = 6W Medium	550	120 - 277V	50K	6.46"	13.183"
150LEDBOP2X6-50	2X6 = 9W Medium	1100	120 - 277V	50K	6.46"	13.183"
150LEDBOP3X6-50	3X6 = 12W Medium	1650	120 - 277V	50K	6.46"	13.183"
150LEDBOP4X6-50	4X6 = 15W Medium	2200	120 - 277V	50K	6.46"	13.183"
150LEDBOP5X6-50	5X6 = 18W Medium	2750	120 - 277V	50K	6.46"	13.183"
150LEDBOP6X6-50	6X6 = 22W Medium	3300	120 - 277V	50K	6.46"	13.183"
150LEDBOP7X6-50	7X6 = 25W Medium	3850	120 - 277V	50K	6.46"	13.183"

Lumens Per 1 X 6" Panel = 3000K = 520 Lumens 3500K = 530 Lumens 4000K = 540 Lumens 5000K = 550 Lumens

Specify Color At The End Of Model Number (-50, -40, -35, -30)

Lumens Per Color Above



**Vertically Integrated Manufacturer
Made In USA**

ENERTRON®

3030-D Enterprise Court
Vista, CA 92081
800-537-7649
Fax 877-708-7777