


**LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON**



**Compact Fluorescent  
Large Metal Canopy Fixture  
300 Series**

- Ceiling Mount Canopy Fixture
- Programmed Start Highest Quality USA Electronic Ballast 120-277V  
*Cross From MH Or HPS To Compact Fluorescent For More Energy Savings*
- Compact Fluorescent From 18 To 84 Watts
- High Power Factor THD< 10% Crest Factor< 1.7, Class A Sound Rating
- Minimum Start Temperature 0°F, -18°C
- UL Wet Location, Gasket Standard
- Textured Bronze Finish Die Cast Aluminum Housing, Chromate Conversion Coating With 3/4" Threaded Hubs For Conduit Fittings, White Reflector
- White Finish Housing Available, (-W)
- Standard Polycarbonate Lens Molded With GE Lexan Containing UV Stabilizers
- Cool White Lamps Standard, Warm White (WW) Available Upon Request
- Photo Cell, Battery Back-Up Available

Model	Lamp Type	Ballast Type	Watts	Ballast Voltage	Initial Lumens	Rated Average Lamp Life	CRI	Height	Width	Depth
30026CFX-L	2x13 Watt	Magnetic	26	120/277	1600	10,000 Hrs.	82	8.5"	12.375"	12.375"
30026QECFX-L	26 Watt	Electronic	26	120/277	1800	10,000 Hrs.	82	8.5"	12.375"	12.375"
30026ECFX-L	26 Watt	Electronic	26	120/277	1800	10,000 Hrs.	82	8.5"	12.375"	12.375"
30032ECFX-L	32 Watt	Electronic	32	120/277	2400	10,000 Hrs.	82	8.5"	12.375"	12.375"
30036ECFX-L	2x18 Watt	Electronic	36	120/277	2400	10,000 Hrs.	82	8.5"	12.375"	12.375"
30042ECFX-L	42 Watt	Electronic	42	120/277	3200	10,000 Hrs.	82	8.5"	12.375"	12.375"
30044CFX-L	2x22 Watt	Magnetic	44	120/277	2600	10,000 Hrs.	82	8.5"	12.375"	12.375"
30052ECFX-L	2x26 Watt	Electronic	52	120/277	3600	10,000 Hrs.	82	8.5"	12.375"	12.375"
30064ECFX-L	2x32 Watt	Electronic	64	120/277	4800	10,000 Hrs.	82	8.5"	12.375"	12.375"
30084ECFX-L	2x42 Watt	Electronic	84	120/277	6400	10,000 Hrs.	82	8.5"	12.375"	12.375"



**Vertically Integrated Manufacturer  
Made In USA**