

LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



7800B-L



7800W-L

**7000 Polycarbonate
Wall Pack Series**

- ADA - Used For Endless Indoor Or Outdoor Applications Can Be Installed Vertically Or Horizontally *For High Abuse Areas Such As: Carports, Stairwells, Corridors, Utility Or Dorm Closets, Or Porches – Commercial & Residential*
- UL Wet Location Wall Mounted
UL Damp Location Ceiling Mounted
- **LEXAN Housing Black (-B) Or White (-W)**
Made In-House - Standard - LEXAN Clear Prismatic Lens - Or Opaque White Add (-OP) White Powder Coated Reflector Standard
- **Gasket Available Upon Request Add (-GAS)**
- Stainless Steel Tamper Resistant 3/32" Allen Head Screws Upon Request – See Lamp Color Options
- **Photocell Available Adder: (-PC)**
- Instant Start Lamps 2 Pin ADD (LI) 13 Watt Lamp Available Upon Request (For Magnetic)
- **Magnetic Ballast** 45,000+ Class P Thermally Protected, Two-Piece Ballast - Lamp 2 pin
- **Electronic Ballast HPF (Add -E)** High Quality USA Engineered, Programmed Start 120-277V 1x13 Watt Only - 4 Pin Lamps
- **Electronic Residential NPF (Add R&E)** Electronic 120V Only Ballast Also Available, (70R26EQB-L) 1x26 Or 1x13 Watt. 4 Pin Lamps

Model	Ballast Type	Lamp Watts		Initial Lumens	Rated Average Lamp/Ballast Life	Dimensions			Min. Start Temp
						D	W	H	
7500-L	Magnetic	9		600	10,000+/45,000+ Hrs.	4"	4.625"	8.562"	20° F
7800-L	Magnetic	13		900	10,000+/45,000+ Hrs.	4"	4.625"	8.562"	20° F
7800E-L	Electronic HPF	13E		900	10,000+/45,000+ Hrs.	4"	4.625"	8.562"	0° F
70R26EQ	Electronic NPF	26E		1800	10,000+/45,000+ Hrs.	4"	4.625"	8.562"	0° F
7026-L	Magnetic	26 (2x13)		1800	10,000+/45,000+ Hrs.	4"	4.625"	8.562"	20° F

*Set Screw Holds Lamp In Place For Versatile Positioning (13, And 26 Watt Units Only)
Warm White Lamps Standard In Magnetic – Electronic Is standard In Cool White*



**Vertically Integrated Manufacturer
Made In USA**