


LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



**Compact Fluorescent
Large Dark Sky
Wall Pack 493 Series**

- Dark Sky Compliant—Full Cut Off
- Programmed Start Electronic Highest Quality USA Ballast 120-277V
Cross From MH Or HPS To Compact Fluorescent For More Energy Savings
- High Power Factor THD< 10% Crest Factor< 1.7, Class A Sound Rating
- Minimum Start Temperature 0°F, -18°C
- UL Wet Location, Gasket Standard
- Flat Tempered Clear Glass Lens With Aluminum Reflector
- Bronze Die Cast Aluminum With ½” Coin Plugs With O Rings For Conduit Fittings
- Hinged FrontFrame Access For Easy Installation
- Compact Fluorescent Available From 36 To 128 Watts
- Cool White Lamps Standard On Electronic Builds, Warm White On Magnetic, Any Color Lamp Available Upon Request
- Photo Cell (-PC) And Battery Back Up (-BB) Options Available
- Stainless Steel Wire Guard (-WG) Option Available
- White Finish Housing Available, (-W)

| Model | Lamp Type | Ballast Type | Watts | Ballast Voltage | Initial Lumens | Rated Average Lamp Life | Height | Width | Depth |
|-------------|-----------|--------------|-------|-----------------|----------------|-------------------------|--------|--------|--------|
| 49352ECF-L | 2x26 Watt | Electronic | 52 | 120 – 277V | 3600 | 10,000 Hrs. | 9.125" | 18.25" | 13.75" |
| 49364ECF-L | 2x32 Watt | Electronic | 64 | 120 – 277V | 4800 | 10,000 Hrs. | 9.125" | 18.25" | 13.75" |
| 49372ECF-L | 4x18 Watt | Electronic | 72 | 120 – 277V | 4800 | 10,000 Hrs. | 9.125" | 18.25" | 13.75" |
| 49384ECF-L | 2x42 Watt | Electronic | 84 | 120 – 277V | 6400 | 10,000 Hrs. | 9.125" | 18.25" | 13.75" |
| 493104ECF-L | 4x26 Watt | Electronic | 104 | 120 – 277V | 7200 | 10,000 Hrs. | 9.125" | 18.25" | 13.75" |
| 493128ECF-L | 4x32 Watt | Electronic | 128 | 120 – 277V | 9600 | 10,000 Hrs. | 9.125" | 18.25" | 13.75" |



**Vertically Integrated Manufacturer
Made In USA**