

LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



150 Version




151 Version



153 Version

- Vandal Resistant Hardware And Materials
- Wet Location, Gasket Included For Back And Lens
- Die-Cast Marine Grade Aluminum Housing Available In 3 Depths: Shallow (S), Standard And Deep (D)
- Polycarbonate Injection Molded Guard Available In 4 Colors: White (W), Black (B) And Bronze (BZ), Titanium (TI)
- Polycarbonate Injection Molded Lens Available In 3 Versions: Opaque (OP), Frosted Ribbed (FR), And Clear Ribbed (CR)
- Guard Comes In 3 Versions Shown On Left: Open Face (150), Eyelid (151) And Cross Guard (153)
- Guard Allows For Drainage Of Moisture With Integral Weep Hole, Pin-in-Head Stainless Steel Tamper Proof Screws Standard
- Cool White Lamps Standard On Electronic Ballast, Warm White On Magnetic, Any Lamp Color Available Upon Request
- Electronic Highest Quality USA Programmed Start Ballast 120-277V, 45,000+ Hour, Class P Thermally Protected
- Magnetic Ballast 120 Volt/60 Hz
- Other Wattage Combinations Available

Model	Watts/ Lamps	Initial Lumens	Ballast Type	Ballast Voltage	Rated Average Lamp/Ballast Life	Dimensions		
						D	W	L
15026EBZOP-L	26 (2x13)	1800	Electronic	120-277	10,000+/45,000+ Hrs.	6.03"	13.183"	13.183"
15126WCR-L	26 (2x13)	1800	Magnetic	120	10,000+/45,000+ Hrs.	6.40"	13.183"	13.183"
15336EBFR-L	36 (2x18)	2500	Electronic	120-277	10,000+/45,000+ Hrs.	6.40"	13.183"	13.183"
15042EBOP-L	42 (1x42)	3200	Electronic	120-277	10,000+/45,000+ Hrs.	6.03"	13.183"	13.183"
15152EWFR-L	52 (2x26)	3600	Electronic	120-277	10,000+/45,000+ Hrs.	6.40"	13.183"	13.183"
15364EBZCR-L	64 (2x32)	4800	Electronic	120-277	10,000+/45,000+ Hrs.	6.40"	13.183"	13.183"



**Vertically Integrated Manufacturer
Made In USA**