


LEADING THE INDUSTRY WITH QUALITY YOU CAN DEPEND ON



**1400 Series Compact
Fluorescent Polycarbonate**

- Wet-Rated Drum, Wall Or Ceiling Mount
- Completely Polycarbonate, Lens & Back Gasket Standard
- 45,000+ Hour Class P Thermally Protected Ballast/10,000+ Hour Replaceable Lamp Life
- **Instant Start Twin Tube (LI) 13 Watt Lamps Upon Request**
- Warm White Lamps Standard, Cool White (CW) Upon Request On Magnetic Build
- Cool White Lamps Standard, Warm White (WW) Upon Request On Electronic Builds
- Polycarbonate Diffuser And Body, Available In Both Round (R) And Square (S) Versions W/ Drilling Templates For Conduit
- Available With Prismatic (PR), Frosted (FR) Or Opaque (OP) Diffuser
- Base Pan Available In White (W) Or Black (B) Polycarbonate
- Programmed Start HPF Electronic Highest Quality USA Ballast Available 120-277VAC (E)
- Electronic Non-Programmed Start, Residential-Graded Ballast Available 120VAC Only (14R)
- LED Now Available – Greatest Energy Savings Long Life –No Lamp Changes – See LED Spec Sheet.

Model	Watts	Ballast Type	Ballast Voltage	Initial Lumens	Rated Average Lamp/Ballast Life	Dimensions	
						W	H
1413ERBXOP-L	13 (1x13)	Electronic PS	120-277	900	10,000+/45,000+ Hrs.	12"	4"
1413SBXOP-L	13 (1x13)	Magnetic	120	900	10,000+/45,000+ Hrs.	10.5"	4"
1426RBXOP-L	26 (2x13)	Magnetic	120	1800	10,000+/45,000+ Hrs.	12"	4"
1426EQRBXOP-L	26 (1x26)	Electronic PS	120-277	1800	10,000+/45,000+ Hrs.	12"	4"
1426ESBXOP-L	26 (2x13)	Electronic PS	120-277	1800	10,000+/45,000+ Hrs.	10.5"	4"
14R26EQRBXOP-L	26 (1x26)	Electronic NPS	120	1800	10,000+/45,000+ Hrs.	12"	4"
1432ERBXOP-L	32 (1x32)	Electronic PS	120	2400	10,000+/45,000+ Hrs.	12"	4"



**Vertically Integrated Manufacturer
Made In USA**